

M. A. Padlipsky  
MIT-MULTICS  
November 14, 1972

Two recently-installed features of the Multics Network software might be of general interest to the Network community, and should be of particular interest to those who use Multics via TIP's:

\_\_\_\_\_

- 1) as most Multics input is lower-case, alphabetic input is mapped to lower-case, except for any letter immediately preceded by "
- 2) back (left) arrow is treated as underscore, up arrow as circumflex, apostrophe as acute (right) accent
- 3) escape sequences exist for the following:
  - backspace = -
  - grave (left) accent = '
  - left brace =
  - vertical line =
  - right brace = )
  - tilde = =
- 4) the sequence "\" is treated as "a " octal escape, it is only necessary to type them

[Page 1]

## Allocate Handling

-----

Output to systems which give small allocations has long been a problem, both to the remote user (who experienced frequent pauses in the output at his terminal) and to the Multics "Network Daemon" process (which encountered considerable inefficiency because of being frequently awakened to process the ALL control messages). To alleviate this, we have introduced interrupt-time code which processes the ALL's and outputs the next group of bytes without causing the Network Daemon to take a wakeup. As attendees of the ICCG will have already observed, response is far superior under the new scheme. (System Programmers responsible for NCP's might be interested to know that some 75% of our control-message processing deals with ALL's.)

[ This RFC was put into machine readable form for entry ]  
[ into the online RFC archives by BBN Corp. under the ]  
[ direction of Alex McKenzie. 1/97 ]

